

PRODUCT DATA SHEETS • ISSUE: OCTOBER 2026

Pipe Hangers & Clamps Data Sheets

Clevis, ring, J and heavy-duty hangers, supports, rod and accessories, and pipe clamps, with full size tables. Larger sizes, special materials and finishes are available on request. UL / FM available.

CONTENTS

TN-HG-CLV Clevis hanger	2	TN-HG-WBH Heavy-duty wall bracket	24
TN-HG-CLVL Light-duty clevis hanger	3	TN-SB-SWY Sway brace pipe attachment	25
TN-HG-CLVC Clevis hanger, copper coated	4	TN-CL-STD Standard pipe clamp	26
TN-HG-CLVI Clevis hanger for insulated pipe	5	TN-CL-RSR Riser clamp	27
TN-HG-CLVH Heavy-duty clevis hanger (ductile and cast iron pipe)	6	TN-CL-RSRC Copper tubing riser clamp	28
TN-HG-CLVP Plastic pipe clevis hanger	7	TN-CL-DS Double-screw pipe clamp	29
TN-HG-RNG Adjustable swivel ring hanger	8	TN-CL-DSL Light double-screw pipe clamp	30
TN-HG-CUP Cup-nut ring hanger	9	TN-CL-HD Heavy-duty pipe clamp	31
TN-HG-RNGC Ring hanger for copper tubing	10	TN-CL-2P Double-bolt (two-piece) pipe clamp	32
TN-HG-RNGN Ring hanger, hanger-nut connection	11	TN-CL-2PH Heavy-duty double-bolt pipe clamp	33
TN-HG-BNDC Copper tubing band hanger	12	TN-CL-SBC Split band clip (metric pipe OD)	34
TN-HG-SPR Split ring hanger	13	TN-CL-SPS Pipe strap (Ohm type)	35
TN-HG-J J-type hanger	14	TN-CL-SHS Short pipe strap	36
TN-HG-UB U-bolt	15	TN-CL-FLT Flat pipe clamp	37
TN-HG-RODM Machine-thread hanger rod	16	TN-CL-ST2C Two-hole strap for copper tubing	38
TN-HG-RCP Rod coupling	17	TN-CL-UG Underground pipe clamp, two-bolt	39
TN-HG-RCR Reducing rod coupling	18	TN-CL-UG4 Underground pipe clamp, four-bolt	40
TN-HG-SHD Insulation protection shield	19	TN-CL-BMC Centre-load beam clamp, standard duty	41
TN-HG-SAD Pipe saddle support with coupling	20	TN-CL-BMCH Centre-load beam clamp, heavy duty	42
TN-HG-SADS Pipe saddle support with stud	21	TN-CL-BMA Adjustable beam clamp	43
TN-HG-WBL Light-duty wall bracket	22	TN-CL-CPV CPVC saddle pipe clamp	44
TN-HG-WBM Medium-duty wall bracket	23		

Approval status. UL Listed and FM Approved grooved fittings, couplings and accessories supplied to project specification. Information in this document is taken from published True North™ product information and is subject to change without notice.

CLEVIS HANGERS · PRODUCT DATA SHEET

Clevis hanger

TN-HG-CLV

UL / FM available

Adjustable clevis for suspending stationary horizontal pipe from threaded rod. Conforms to MSS SP-58 Type 1.

Part no.	TN-HG-CLV
Sizes	1/2" to 12". Larger sizes available on request.
Material / finish	Carbon steel, electro-galvanized; 304 / 316 stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
1/2"	3/8"	299
3/4"	3/8"	299
1"	3/8"	299
1-1/4"	3/8"	299
1-1/2"	3/8"	299
2"	3/8"	299
2-1/2"	1/2"	339
3"	1/2"	419
3-1/2"	1/2"	499
4"	5/8"	599
5"	5/8"	799
6"	3/4"	1,059
8"	7/8"	1,619
10"	7/8"	2,339
12"	7/8"	3,159

CLEVIS HANGERS · PRODUCT DATA SHEET

Light-duty clevis hanger

TN-HG-CLVL

UL / FM available

Clevis hanger for non-insulated pipe in light-duty applications. MSS SP-58 Type 1.

Part no.	TN-HG-CLVL
Sizes	1/2" to 6". Larger sizes available on request.
Material / finish	Carbon steel, pre-galvanized (1/2" to 4") or electro-galvanized (5" to 6")
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
1/2"	3/8"	150
3/4"	3/8"	250
1"	3/8"	250
1-1/4"	3/8"	250
1-1/2"	3/8"	250
2"	3/8"	250
2-1/2"	1/2"	350
3"	1/2"	350
3-1/2"	1/2"	350
4"	1/2"	400
5"	5/8"	400
6"	3/4"	400

CLEVIS HANGERS · PRODUCT DATA SHEET

Clevis hanger, copper coated

TN-HG-CLVC

UL / FM available

Clevis hanger for non-insulated copper tubing. MSS SP-58 Type 1.

Part no.	TN-HG-CLVC
Sizes	1/2" to 6". Larger sizes available on request.
Material / finish	Carbon steel, copper-colour coating
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
1/2"	3/8"	299
3/4"	3/8"	299
1"	3/8"	299
1-1/4"	3/8"	299
1-1/2"	3/8"	299
2"	3/8"	299
2-1/2"	1/2"	339
3"	1/2"	419
3-1/2"	1/2"	499
4"	5/8"	599
5"	5/8"	799
6"	3/4"	1,059

CLEVIS HANGERS · PRODUCT DATA SHEET

Clevis hanger for insulated pipe

TN-HG-CLVI

UL / FM available

Elongated clevis that lets the insulation pass through the hanger. MSS SP-58 Type 1.

Part no.	TN-HG-CLVI
Sizes	1/2" to 12". Larger sizes available on request.
Material / finish	Carbon steel, plain or electro-galvanized; hot-dip galvanized or stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
1/2"	3/8"	730
3/4"	3/8"	730
1"	3/8"	730
1-1/4"	3/8"	730
1-1/2"	3/8"	730
2"	3/8"	730
2-1/2"	1/2"	1,350
3"	1/2"	1,350
3-1/2"	5/8"	1,350
4"	5/8"	1,430
5"	3/4"	1,430
6"	3/4"	1,940
8"	3/4"	2,000
10"	7/8"	3,600
12"	7/8"	3,800

CLEVIS HANGERS · PRODUCT DATA SHEET

Heavy-duty clevis hanger (ductile and cast iron pipe)

TN-HG-CLVH

UL / FM available

Heavy clevis for ductile iron and cast iron water pipe. MSS SP-58 Type 1.

Part no.	TN-HG-CLVH
Sizes	3" to 36"
Material / finish	Carbon steel, plain or electro-galvanized; hot-dip galvanized or stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
3"	1/2"	1,350
4"	5/8"	1,430
6"	3/4"	1,940
8"	3/4"	2,000
10"	7/8"	3,600
12"	7/8"	3,800
14"	1"	4,200
16"	1"	4,600
18"	1"	4,800
20"	1-1/4"	4,800
24"	1-1/4"	4,800
30"	1-1/4"	4,800
36"	1-1/2"	

CLEVIS HANGERS · PRODUCT DATA SHEET

Plastic pipe clevis hanger

TN-HG-CLVP

UL / FM available

Clevis for flexible plastic pipe, used with a support trough.

Part no.	TN-HG-CLVP
Sizes	1/2" to 4". Larger sizes available on request.
Material / finish	Carbon steel, plain or electro-galvanized; stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
1/2"	3/8"	150
3/4"	3/8"	150
1"	3/8"	150
1-1/4"	3/8"	150
1-1/2"	3/8"	150
2"	3/8"	150
2-1/2"	5/8"	150
3"	5/8"	150
3-1/2"	5/8"	150
4"	5/8"	150

OTHER SUPPORTS & ACCESSORIES · PRODUCT DATA SHEET

Adjustable swivel ring hanger

TN-HG-RNG

UL / FM available

Swivel ring (band) hanger with knurled insert nut for vertical adjustment after installation. MSS SP-58 Type 10.

Part no.	TN-HG-RNG
Sizes	1/2" to 12". Larger sizes available on request.
Material / finish	Carbon steel, pre-galvanized (to 8") or electro-galvanized (10" to 12"); PVC-coated version available
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
1/2"	3/8"	299
3/4"	3/8"	299
1"	3/8"	299
1-1/4"	3/8"	299
1-1/2"	3/8"	299
2"	3/8"	299
2-1/2"	3/8"	339
3"	3/8"	419
3-1/2"	3/8"	499
4"	3/8"	599
5"	1/2"	799
6"	1/2"	1,059
10"	5/8"	2,339
12"	5/8"	3,159
8"	1/2"	1,619

OTHER SUPPORTS & ACCESSORIES · PRODUCT DATA SHEET

Cup-nut ring hanger

TN-HG-CUP

UL / FM available

Ring hanger with cup nut, adjustable vertically. MSS SP-58 Type 9.

Part no.	TN-HG-CUP
Sizes	1" to 8". Larger sizes available on request.
Material / finish	Carbon steel, pre-galvanized
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
1"	5/16"	299
1-1/4"	5/16"	299
1-1/2"	5/16"	299
2"	5/16"	299
2-1/2"	3/8"	499
3"	3/8"	599
4"	3/8"	799
5"	3/8"	1,059
6"	3/8"	1,619
8"	3/8"	1,619

OTHER SUPPORTS & ACCESSORIES · PRODUCT DATA SHEET

Ring hanger for copper tubing

TN-HG-RNGC

UL / FM available

Ring hanger for non-insulated copper tubing. MSS SP-58 Type 10.

Part no.	TN-HG-RNGC
Sizes	1/2" to 6". Larger sizes available on request.
Material / finish	Carbon steel, black or copper-colour coating
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
1/2"	3/8"	299
3/4"	3/8"	299
1"	3/8"	299
1-1/4"	3/8"	299
1-1/2"	3/8"	299
2"	3/8"	299
2-1/2"	3/8"	339
3"	3/8"	419
3-1/2"	3/8"	499
4"	3/8"	599
5"	1/2"	799
6"	1/2"	1,059

OTHER SUPPORTS & ACCESSORIES · PRODUCT DATA SHEET

Ring hanger, hanger-nut connection

TN-HG-RNGN

UL / FM available

Ring hanger with hanger-nut connection. MSS SP-58 Type 7.

Part no.	TN-HG-RNGN
Sizes	1/2" to 8". Larger sizes available on request.
Material / finish	Carbon steel, pre-galvanized
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
1/2"	3/8"	299
3/4"	3/8"	299
1"	3/8"	299
1-1/4"	3/8"	299
1-1/2"	3/8"	299
2"	3/8"	299
2-1/2"	3/8"	339
3"	3/8"	419
3-1/2"	3/8"	499
4"	3/8"	599
5"	1/2"	799
6"	1/2"	1,059
8"	1/2"	1,619

OTHER SUPPORTS & ACCESSORIES · PRODUCT DATA SHEET

Copper tubing band hanger

TN-HG-BNDC

UL / FM available

Band hanger for copper tubing with hanger-nut connection. MSS SP-58 Type 7.

Part no.	TN-HG-BNDC
Sizes	1/2" to 4". Larger sizes available on request.
Material / finish	Carbon steel, copper-colour epoxy
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
1/2"	3/8"	299
3/4"	3/8"	299
1"	3/8"	299
1-1/4"	3/8"	299
1-1/2"	3/8"	299
2"	3/8"	299
2-1/2"	3/8"	339
3"	3/8"	419
3-1/2"	3/8"	499
4"	3/8"	599

OTHER SUPPORTS & ACCESSORIES · PRODUCT DATA SHEET

Split ring hanger

TN-HG-SPR

UL / FM available

Hinged split ring hanger for horizontal or vertical pipe. MSS SP-58 Type 12.

Part no.	TN-HG-SPR
Sizes	3/8" to 4". Larger sizes available on request.
Material / finish	304 stainless steel
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
3/8"	3/8"	180
1/2"	3/8"	180
3/4"	3/8"	180
1"	3/8"	180
1-1/4"	3/8"	180
1-1/2"	3/8"	180
2"	3/8"	180
3"	1/2"	299
4"	1/2"	299

OTHER SUPPORTS & ACCESSORIES · PRODUCT DATA SHEET

J-type hanger

TN-HG-J

UL / FM available

J hanger with T-slot so the side bolt can be fitted after the pipe is set; side hole for wall mounting. MSS SP-58 Type 5.

Part no.	TN-HG-J
Sizes	1/2" to 12". Larger sizes available on request.
Material / finish	Carbon steel, electro-galvanized
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
1/2"	3/8"	299
3/4"	3/8"	299
1"	3/8"	299
1-1/4"	3/8"	299
1-1/2"	3/8"	299
2"	3/8"	299
2-1/2"	3/8"	339
3"	3/8"	419
3-1/2"	3/8"	499
4"	3/8"	599
5"	1/2"	799
6"	1/2"	1,059
8"	5/8"	1,619
10"	5/8"	2,339
12"	5/8"	3,159

OTHER SUPPORTS & ACCESSORIES · PRODUCT DATA SHEET

U-bolt

TN-HG-UB

UL / FM available

Support, anchor or guide for pipe. MSS SP-58 Type 24.

Part no.	TN-HG-UB
Sizes	1/2" to 12". Larger sizes available on request.
Material / finish	Carbon steel, electro-galvanized
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod size	Max. rec. load (lb)
1/2"	1/4" / 3/8"	1,460
3/4"	1/4" / 3/8"	1,460
1"	1/4" / 3/8"	1,460
1-1/4"	1/4" / 3/8"	1,460
1-1/2"	1/4" / 3/8"	1,460
2"	1/4" / 3/8"	1,460
2-1/2"	3/8" / 1/2"	2,700
3"	3/8" / 1/2"	2,700
3-1/2"	3/8" / 1/2"	2,700
4"	3/8" / 1/2"	2,700
5"	3/8" / 1/2"	2,700
6"	1/2" / 5/8"	4,320
8"	1/2" / 5/8"	4,320
10"	5/8" / 3/4"	6,460
12"	7/8"	8,960

OTHER SUPPORTS & ACCESSORIES · PRODUCT DATA SHEET

Machine-thread hanger rod

TN-HG-RODM

UL / FM available

Hanger rod for pipe hanger assemblies; lengths to order.

Part no.	TN-HG-RODM
Sizes	3/8" to 1"
Material / finish	Carbon steel, plain or electro-galvanized
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Rod size (in)	Max. rec. load (lb)
3/8"	730
1/2"	1,350
5/8"	2,160
3/4"	3,230
7/8"	4,480
1"	5,900

OTHER SUPPORTS & ACCESSORIES · PRODUCT DATA SHEET

Rod coupling

TN-HG-RCP

UL / FM available

Joins two lengths of threaded rod of equal diameter.

Part no.	TN-HG-RCP
Sizes	1/4" to 1"
Material / finish	Carbon steel, electro-galvanized
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Rod size	Thread	Max. rec. load (lb)
1/4"	1/4"	240
3/8"	3/8"	730
1/2"	1/2"	1,350
5/8"	5/8"	2,160
3/4"	3/4"	3,230
7/8"	7/8"	4,480
1"	1"	5,900

OTHER SUPPORTS & ACCESSORIES · PRODUCT DATA SHEET

Reducing rod coupling

TN-HG-RCR

UL / FM available

Joins two lengths of threaded rod of different diameters.

Part no.	TN-HG-RCR
Sizes	3/8X1/4 to 7/8X3/4
Material / finish	Carbon steel, plain or electro-galvanized
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Rod sizes (in)	Max. rec. load (lb)
3/8" x 1/4"	240
1/2" x 3/8"	730
5/8" x 1/2"	1,350
3/4" x 5/8"	2,160
7/8" x 3/4"	3,230

OTHER SUPPORTS & ACCESSORIES · PRODUCT DATA SHEET

Insulation protection shield

TN-HG-SHD

UL / FM available

Shields that protect pipe insulation at the hanger. MSS SP-58 Type 40.

Part no.	TN-HG-SHD
Sizes	2" to 30" pipe. Larger sizes available on request.
Material / finish	Carbon steel, pre-galvanized; stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size x shield I.D. (x gauge)	Rod	Max. rec. load (lb)	Pipe size x shield I.D. (x gauge)	Rod	Max. rec. load (lb)	Pipe size x shield I.D. (x gauge)	Rod	Max. rec. load (lb)	Pipe size x shield I.D. (x gauge)	Rod	Max. rec. load (lb)
2" x 2-3/8"	3/8"	300	6"			12"			20"		
2"			6"			12"			20"		
2-1/2" x 2-5/8"	3/8"	525	8" x 7-5/8"	1/2"	1,000	14" x 14"			20" x 20"		
2-1/2" x 2-7/8"	3/8"	525	8"			14"			20"		
2-1/2"			8"			14"			20"		
2-1/2"			8" x 8-5/8"	1/2"	1,000	3-1/2" x 4"	3/8"	525	20"		
3" x 3-1/2"	3/8"	525	8"			16" x 15"			24" x 21"		
3"			8"			16"			24"		
3-1/2"			10" x 10-3/4"	7/8"		16"			24"		
4" x 4-1/2"	3/8"	650	10"			16" x 16"			24"		
4"			10"			16"			24"		
5" x 5"	1/2"	1,000	10"			16"			24"		
5" x 5-5/8"	1/2"	1,000	10" x 9-5/8"	7/8"		18" x 17"			24"		
5"			10"			18"			24"		
5"			10"			18"			24"		
5"			12" x 10-3/4"	7/8"		18" x 18"			30"		
6" x 6"	1/2"	1,000	12" x 11-3/4"			18"			30"		
6" x 6-5/8"	1/2"	1,000	12"			18"			30"		
6"			12"			18"			30"		
6"			12" x 12-3/4"	7/8"		20" x 19"					

OTHER SUPPORTS & ACCESSORIES · PRODUCT DATA SHEET

Pipe saddle support with coupling

TN-HG-SAD

UL / FM available

Saddle for horizontal pipe on floor stanchions, used with a threaded base stand.

Part no.	TN-HG-SAD
Sizes	1-1/2" to 12". Larger sizes available on request.
Material / finish	Carbon steel, plain or electro-galvanized; stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size
1-1/2"
2"
2-1/2"
3"
3-1/2"
4"
5"
6"
8"
10"
12"

OTHER SUPPORTS & ACCESSORIES · PRODUCT DATA SHEET

Pipe saddle support with stud

TN-HG-SADS

UL / FM available

Saddle with stud for horizontal pipe close to the floor, with vertical adjustment.

Part no.	TN-HG-SADS
Sizes	2-1/2" to 36"
Material / finish	Carbon steel, plain or electro-galvanized; hot-dip galvanized or stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Max. rec. load (lb)
2-1/2"	1,800
3"	1,800
3-1/2"	1,800
4"	3,800
5"	3,800
6"	3,800
8"	3,800
10"	3,800
12"	3,800
14"	5,300
16"	5,300
18"	6,700
20"	6,700
24"	7,300
30"	7,300
36"	7,300

OTHER SUPPORTS & ACCESSORIES · PRODUCT DATA SHEET

Light-duty wall bracket

TN-HG-WBL

UL / FM available

Welded steel bracket for suspending hanger rod from walls; loads up to 750 lb. MSS SP-58 Type 31.

Part no.	TN-HG-WBL
Sizes	9" (229 mm) to 19" (483 mm)
Material / finish	Carbon steel, plain or electro-galvanized; hot-dip galvanized or stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Bracket size	Max. rec. load (lb)
9"	750
13"	750
19"	750

OTHER SUPPORTS & ACCESSORIES · PRODUCT DATA SHEET

Medium-duty wall bracket

TN-HG-WBM

UL / FM available

Welded steel bracket for loads up to 1,500 lb from walls or structures. MSS SP-58 Type 32.

Part no.	TN-HG-WBM
Sizes	18" (457 mm) to 30" (762 mm)
Material / finish	Carbon steel, plain or electro-galvanized; hot-dip galvanized or stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Bracket size	Max. rec. load (lb)
18"	1,500
24"	1,500
30"	1,500

OTHER SUPPORTS & ACCESSORIES · PRODUCT DATA SHEET

Heavy-duty wall bracket

TN-HG-WBH

UL / FM available

Welded steel bracket for loads up to 3,000 lb from walls or structures. MSS SP-58 Type 33.

Part no.	TN-HG-WBH
Sizes	18" (457 mm) to 50" (1270 mm)
Material / finish	Carbon steel, plain or electro-galvanized; hot-dip galvanized or stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Bracket size	Max. rec. load (lb)
18"	3,000
24"	3,000
30"	3,000
36"	3,000
42"	3,000
50"	3,000

OTHER SUPPORTS & ACCESSORIES · PRODUCT DATA SHEET

Sway brace pipe attachment

TN-SB-SWY

UL / FM available

Braces pipe against sway and seismic movement.

Part no.	TN-SB-SWY
Sizes	1/2" to 12". Larger sizes available on request.
Material / finish	Carbon steel, electro-galvanized; hot-dip galvanized on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Max. rec. load (lb)
1/2"	299
3/4"	299
1"	299
1-1/4"	299
1-1/2"	299
2"	299
2-1/2"	339
3"	419
3-1/2"	499
4"	599
5"	799
6"	1,059
8"	1,619
10"	2,339
12"	3,159

PIPE CLAMPS · PRODUCT DATA SHEET

Standard pipe clamp

TN-CL-STD

UL / FM available

Bolted pipe clamp for non-insulated pipe, with bolts and nuts on both sides. MSS SP-58 Type 4.

Part no.	TN-CL-STD
Sizes	1/2" to 8". Larger sizes available on request.
Material / finish	Carbon steel, electro-galvanized; hot-dip galvanized or 316 stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
1/2"	5/16"	299
3/4"	5/16"	299
1"	5/16"	299
1-1/4"	5/16"	299
1-1/2"	5/16"	299
2"	1/2"	299
2-1/2"	1/2"	339
3"	1/2"	419
3-1/2"	1/2"	499
4"	1/2"	599
5"	1/2"	799
6"	1/2"	1,059
8"	1/2"	1,619

PIPE CLAMPS · PRODUCT DATA SHEET

Riser clamp

TN-CL-RSR

UL / FM available

Supports vertical pipe and risers. MSS SP-58 Type 8.

Part no.	TN-CL-RSR
Sizes	1/2" to 12". Larger sizes available on request.
Material / finish	Carbon steel, electro-galvanized; hot-dip galvanized or 316 stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
1/2"	3/8"	299
3/4"	3/8"	299
1"	3/8"	299
1-1/4"	3/8"	299
1-1/2"	3/8"	299
2"	1/2"	299
2-1/2"	1/2"	339
3"	1/2"	419
3-1/2"	1/2"	499
4"	1/2"	599
5"	1/2"	799
6"	1/2"	1,059
8"	5/8"	1,619
10"	5/8"	2,339
12"	5/8"	3,159

PIPE CLAMPS · PRODUCT DATA SHEET

Copper tubing riser clamp

TN-CL-RSRC

UL / FM available

Supports vertical copper tubing runs. MSS SP-58 Type 8.

Part no.	TN-CL-RSRC
Sizes	1/2" to 6". Larger sizes available on request.
Material / finish	Carbon steel, copper-colour coating
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
1/2"	3/8"	299
3/4"	3/8"	299
1"	3/8"	299
1-1/4"	3/8"	299
1-1/2"	3/8"	299
2"	1/2"	299
2-1/2"	1/2"	339
3"	1/2"	419
3-1/2"	1/2"	499
4"	1/2"	599
5"	1/2"	799
6"	1/2"	1,059

PIPE CLAMPS · PRODUCT DATA SHEET

Double-screw pipe clamp

TN-CL-DS

UL / FM available

Two-screw clamp for horizontal or vertical pipe; rubber-lined or plain. MSS SP-58 Type 12.

Part no.	TN-CL-DS
Sizes	1/2" to 12". Larger sizes available on request.
Material / finish	Carbon steel with EPDM liner, electro-galvanized or hot-dip galvanized
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
3/4"	3/8"	299
1"	3/8"	299
1-1/4"	3/8"	299
1/2"	3/8"	299
2"	3/8"	299
1-1/2"	5/16"	299
2-1/2"	3/8"	339
3"	3/8"	419
3-1/2"	3/8"	499
4"	1/2"	599
5"	1/2"	799
6"	1/2"	1,059
8"	5/8"	1,619
10"	5/8"	2,339
12"	5/8"	3,159

PIPE CLAMPS · PRODUCT DATA SHEET

Light double-screw pipe clamp

TN-CL-DSL

UL / FM available

Light-duty two-screw clamp with EPDM liner; wall-plug version available.

Part no.	TN-CL-DSL
Sizes	3/8" to 8". Larger sizes available on request.
Material / finish	Carbon steel with EPDM liner, electro-galvanized
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
1/2"	5/16"	50
3/4"	5/16"	50
1"	5/16"	50
1-1/4"	5/16"	50
1-1/2"	5/16"	50
1-3/4"	5/16"	50
2"	5/16"	50
2-1/2"	5/16"	50
3"	5/16"	50
3-1/2"	5/16"	50
4"		50
5"		97
6"		97
3/8"		50
8"		97

PIPE CLAMPS · PRODUCT DATA SHEET

Heavy-duty pipe clamp

TN-CL-HD

UL / FM available

Pipe clamp for heavier suspended loads. MSS SP-58 Type 4.

Part no.	TN-CL-HD
Sizes	3" to 42"
Material / finish	Carbon steel, plain or electro-galvanized; hot-dip galvanized or stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
3"	3/4"	3,370
3-1/2"	3/4"	3,370
4"	7/8"	3,515
5"	7/8"	3,515
6"	1"	4,865
8"	1"	4,865
10"	1-1/4"	6,010
12"	1-1/2"	8,675
14"	1-1/2"	9,120
16"	1-1/2"	9,120
18"	2"	13,800
20"	2"	15,300
24"	2-1/4"	16,300
28"	2-1/4"	18,000
30"	2-1/2"	20,500
32"	2-1/2"	23,750
34"	2-1/2"	25,000
36"	2-3/4"	28,000
42"	2-3/4"	35,000

PIPE CLAMPS · PRODUCT DATA SHEET

Double-bolt (two-piece) pipe clamp

TN-CL-2P

UL / FM available

Two-piece double-bolt clamp, including for high-temperature insulated pipe. MSS SP-58 Type 3.

Part no.	TN-CL-2P
Sizes	3/4" to 24". Larger sizes available on request.
Material / finish	Carbon steel, plain or electro-galvanized; hot-dip galvanized or stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
3/4"	3/8"	950
1"	3/8"	950
1-1/4"	3/8"	950
1-1/2"	1/2"	1,545
2"	1/2"	1,545
2-1/2"	1/2"	1,545
3"	1/2"	1,545
3-1/2"	1/2"	1,545
4"	5/8"	2,500
5"	5/8"	2,500
6"	3/4"	2,865
8"	3/4"	2,865
10"	7/8"	3,240
12"	7/8"	3,240
14"	7/8"	4,300
16"	7/8"	4,300
18"	1"	4,300
20"	1-1/8"	4,500
24"	1-1/4"	5,490

PIPE CLAMPS · PRODUCT DATA SHEET

Heavy-duty double-bolt pipe clamp

TN-CL-2PH

UL / FM available

Heavy two-piece double-bolt clamp. MSS SP-58 Type 3.

Part no.	TN-CL-2PH
Sizes	6" to 36"
Material / finish	Carbon steel, plain or electro-galvanized; hot-dip galvanized or stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
6"	1"	3,500
8"	1"	4,800
10"	1-1/4"	5,500
12"	1-1/2"	7,000
14"	1-1/2"	9,500
16"	1-1/2"	10,000
18"	2"	13,800
20"	2"	15,300
24"	2"	16,300
28"	2-1/4"	18,000
30"	2-1/4"	20,500
32"	2-1/2"	23,750
34"	2-1/2"	25,000
36"	2-3/4"	28,000

PIPE CLAMPS · PRODUCT DATA SHEET

Split band clip (metric pipe OD)

TN-CL-SBC

UL / FM available

Bolted split band clip sized by pipe outside diameter. MSS SP-58 Type 4.

Part no.	TN-CL-SBC
Sizes	15 mm to 406 mm pipe OD. Larger sizes available on request.
Material / finish	Carbon steel, electro-galvanized
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe OD (mm)	Bolt	Pipe OD (mm)	Bolt	Pipe OD (mm)	Bolt
1/4"	5/16"	5"	3/8"	10"	1/2"
1/2"	5/16"	5"	3/8"	10"	1/2"
3/4"	5/16"	5"	3/8"	10"	1/2"
1"	5/16"	5"	3/8"	10"	5/8"
1-1/4"	3/8"	6"	1/2"	10"	5/8"
1-1/4"	3/8"	6"	1/2"	10"	5/8"
1-1/2"	3/8"	6"	1/2"	12"	5/8"
1-1/2"	3/8"	6"	1/2"	12"	5/8"
2"	3/8"	6"	1/2"	12"	5/8"
2-1/2"	3/8"	6"	1/2"	12"	5/8"
3"	3/8"	6"	1/2"	14"	5/8"
3"	3/8"	8"	1/2"	14"	5/8"
3"	3/8"	8"	1/2"	14"	5/8"
3-1/2"	3/8"	8"	1/2"	14"	5/8"
4"	3/8"	8"	1/2"	16"	5/8"
4"	3/8"	8"	1/2"	16"	5/8"
4"	3/8"	8"	1/2"		
4"	3/8"	8"	1/2"		

PIPE CLAMPS · PRODUCT DATA SHEET

Pipe strap (Ohm type)

TN-CL-SPS

UL / FM available

Holds pipe flush with the mounting surface. MSS SP-58 Type 26.

Part no.	TN-CL-SPS
Sizes	1/2" to 12". Larger sizes available on request.
Material / finish	Carbon steel, electro-galvanized or hot-dip galvanized
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Max. rec. load (lb)
1/2"	299
3/4"	299
1"	299
1-1/4"	299
1-1/2"	299
2"	299
2-1/2"	339
3"	419
3-1/2"	499
4"	599
5"	799
6"	1,059
8"	1,619
10"	2,339
12"	3,159

PIPE CLAMPS · PRODUCT DATA SHEET

Short pipe strap

TN-CL-SHS

UL / FM available

Short strap that holds pipe flush with the mounting surface.

Part no.	TN-CL-SHS
Sizes	1/2" to 2". Larger sizes available on request.
Material / finish	Carbon steel, electro-galvanized
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Max. rec. load (lb)
1/2"	300
3/4"	300
1"	300
1-1/4"	300
1-1/2"	300
2"	300

PIPE CLAMPS · PRODUCT DATA SHEET

Flat pipe clamp

TN-CL-FLT

UL / FM available

Flat clamp for horizontal or vertical pipe; nylon-coated version for copper and stainless steel pipe.

Part no.	TN-CL-FLT
Sizes	1/2" to 10". Larger sizes available on request.
Material / finish	Carbon steel, electro-galvanized or black nylon coating
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Rod / bolt	Max. rec. load (lb)
1/2"	1/2"	692
3/4"	1/2"	749
1"	1/2"	800
1-1/4"	1/2"	895
1-1/2"	1/2"	1,003
2"	1/2"	1,306
2-1/2"	1/2"	1,549
3"	1/2"	1,621
4"	1/2"	1,913
5"	1/2"	2,293
6"	1/2"	2,545
8"	1/2"	2,756
10"	1/2"	3,305

PIPE CLAMPS · PRODUCT DATA SHEET

Two-hole strap for copper tubing

TN-CL-ST2C

UL / FM available

Light-duty two-hole strap for copper tubing.

Part no.	TN-CL-ST2C
Sizes	1/4" to 2". Larger sizes available on request.
Material / finish	Carbon steel, copper-colour epoxy
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Tube size
1/4"
3/8"
1/2"
3/4"
1"
1-1/4"
1-1/2"
2"

PIPE CLAMPS · PRODUCT DATA SHEET

Underground pipe clamp, two-bolt

TN-CL-UG

UL / FM available

Clamps the joints of underground ductile iron water pipe to prevent separation; used with tie rods.

Part no.	TN-CL-UG
Sizes	3" to 36"
Material / finish	Carbon steel, plain or electro-galvanized; hot-dip galvanized or stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Tie rod
3"	3/4"
4"	3/4"
6"	3/4"
8"	3/4"
10"	3/4"
12"	3/4"
14"	1"
16"	1-1/8"
18"	1-1/4"
20"	1-3/8"
24"	1-1/2"
30"	1-3/4"
36"	1-3/4"

PIPE CLAMPS · PRODUCT DATA SHEET

Underground pipe clamp, four-bolt

TN-CL-UG4

UL / FM available

Four-bolt version for underground ductile iron water pipe joints.

Part no.	TN-CL-UG4
Sizes	4" to 24". Larger sizes available on request.
Material / finish	Carbon steel, plain or electro-galvanized; hot-dip galvanized or stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size	Tie rod
4"	3/4"
6"	3/4"
8"	3/4"
10"	1"
12"	1"
14"	1-1/4"
16"	1-1/4"
18"	1-1/4"
20"	1-3/8"
24"	1-1/2"

PIPE CLAMPS · PRODUCT DATA SHEET

Centre-load beam clamp, standard duty

TN-CL-BMC

UL / FM available

Hangs rod from the centre of an I-beam, with the load shared on both sides of the flange. MSS SP-58 Type 21.

Part no.	TN-CL-BMC
Sizes	3X7/16 to 12X1 1/4
Material / finish	Carbon steel, plain or electro-galvanized; hot-dip galvanized or stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Size (flange width × max. thickness)	Max. rec. load (lb)
3" x 7/16"	1,000
4" x 1/2"	1,000
5" x 5/8"	1,000
6" x 3/4"	1,000
7" x 7/8"	1,000
8" x 7/8"	1,000
9" x 1"	1,000
10" x 1"	1,000
11" x 1"	1,000
12" x 1-1/4"	1,000

PIPE CLAMPS · PRODUCT DATA SHEET

Centre-load beam clamp, heavy duty

TN-CL-BMCH

UL / FM available

Heavy-duty centre-load beam clamp. MSS SP-58 Type 21.

Part no.	TN-CL-BMCH
Sizes	4X1/2 to 12X1 1/4
Material / finish	Carbon steel, plain or electro-galvanized; hot-dip galvanized or stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Size (flange width × max. thickness)	Max. rec. load (lb)
4" x 1/2"	3,000
5" x 5/8"	3,000
6" x 3/4"	3,000
7" x 7/8"	3,000
8" x 7/8"	3,000
9" x 1"	3,000
10" x 1"	3,000
11" x 1"	3,000
12" x 1-1/4"	3,000

PIPE CLAMPS · PRODUCT DATA SHEET

Adjustable beam clamp

TN-CL-BMA

UL / FM available

Adjustable for flange widths of 3-1/2" to 8" and flange thicknesses up to 1/2". MSS SP-58 Type 27.

Part no.	TN-CL-BMA
Sizes	3/8" to 3/4"
Material / finish	Carbon steel, plain or electro-galvanized; hot-dip galvanized or stainless steel on request
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Rod size	Max. rec. load (lb)
3/8"	300
1/2"	700
5/8"	1,000
3/4"	1,800

PIPE CLAMPS · PRODUCT DATA SHEET

CPVC saddle pipe clamp

TN-CL-CPV

UL / FM available

Saddle clamp for CPVC sprinkler pipe, supplied with mounting screws.

Part no.	TN-CL-CPV
Sizes	3/4" to 2". Larger sizes available on request.
Material / finish	Carbon steel, pre-galvanized
Approvals	UL / FM available. See Quality & Approvals; contact us for project requirements.
Installation	Install in accordance with NFPA 13, the project specifications and the authority having jurisdiction.

Sizes

Dimensions in inches unless shown otherwise. Loads are maximum recommended loads (lb). Full dimensions on request.

Pipe size
3/4"
1"
1-1/4"
1-1/2"
2"